

Facade Drainage

Reliable water retention system for terraces, facades and flat roofs.





Facade Drainage

Reliable water retention system for terraces, facades and flat roofs.

1 Requirements

- fast and reliable removal of surface water on facades, flat roofs and terraces
- compliance with the guidelines and the flat roof relevant DIN standards
- backwater reserve for sudden accumulation of rainwater

2 Application areas

- flat roof green areas
- passable roof areas and terraces
- facade channels
- in front of entrances of balconies and terraces

3 Solutions

- powerful backwater reserve for abruptly accumulated water quantities
- horizontal and vertical drainage
- effective protection of walls, doors and windows elements
- open channel systems: channel bodies have drainage possibility on all sides
- barrier-free transitions on terraces
- easy assembling kit



Europa Shopping Centre in Bystrica, Slovakia



Holiday Inn in Bydgoszcz, Poland



Centre for Conservative Medicine, Leipzig, Germany



Leonardo Royal Hotel in Munich, Germany



Penthouse in Wiehl, Germany



Retirement home Hennet, Germany

**RECYFIX®
PRO**

**RECYFIX®
PLUS**

**RECYFIX®
STANDARD**

Facade Drainage

**SLOTTED
CHANNELS**

**RECYFIX® POINT
FASERFIX® POINT**

**RECYFIX®
GREEN**

TOP X


DACHFIX®POINT **NEW**

Gully-extension

DACHFIX®POINT Type 30 x 30



Frame for Gully-extension
30 x 30, type 55



Frame for Gully-extension
30 x 30, type 70



Frame for Gully-extension
30 x 30, type 150

	Length mm	Width mm	Height mm	Weight kg	Item-No. galvanised	Item-No. stainless steel
Frame for Gully-extension 30 x 30, type 55	30	30	55	0,83	65321	65371
Frame for Gully-extension 30 x 30, type 70	30	30	70	0,95	65322	65372
Frame for Gully-extension 30 x 30, type 150	30	30	150	1,60	65323	65373

The quality of stainless steel material corresponds to CNS 1.4301.
DACHFIX POINT gullies are walkable and wheelchair passable.

Gratings

DACHFIX®POINT Type 30 x 30



Mesh grating MW 30/10 mm
for Gully-extension
Type 30 x 30



Gully-extension Type 30 x 30
with Longitudinal grating,
galvanised

	Length mm	Width mm	Height mm	Weight kg	Item-No. galvanised	Item-No. stainless steel
Mesh grating MW 30/10 mm for Gully-extension Type 30 x 30	290	290	20	2,02	65327	65377
Gully-extension Type 30 x 30 with Longitudinal grating, galvanised	290	290	20	3,15	65329	65379

The quality of stainless steel material corresponds to CNS 1.4301.
DACHFIX POINT gullies are walkable and wheelchair passable.

DACHFIX®POINT **NEW**

Gully-extension

DACHFIX®POINT Type 40 x 40



Frame for Gully-extension
40 x 40, type 55

Frame for Gully-extension
40 x 40, type 70

Frame for Gully-extension
40 x 40, type 150

	Length mm	Width mm	Height mm	Weight kg	Item-No. galvanised	Item-No. stainless steel
Frame for Gully-extension 40 x 40, type 55	40	40	55	1,12	65421	65471
Frame for Gully-extension 40 x 40, type 70	40	40	70	1,27	65422	65472
Frame for Gully-extension 40 x 40, type 150	40	40	150	2,13	65423	65473

The quality of stainless steel material corresponds to CNS 1.4301.
DACHFIX POINT gullies are walkable and wheelchair passable.

Gratings

DACHFIX®POINT Type 40 x 40



Mesh grating MW 30/10
for Gully-extension
Type 40 x 40

Gully-extension Type 40 x 40
with Longitudinal grating,
galvanised

	Length mm	Width mm	Height mm	Weight kg	Item-No. galvanised	Item-No. stainless steel
Mesh grating MW 30/10 for Gully-extension Type 40 x 40	390	390	20	3,48	65427	65477
Gully-extension Type 40 x 40 with Longitudinal grating, galvanised	390	390	20	5,40	65429	65479

The quality of stainless steel material corresponds to CNS 1.4301.
DACHFIX POINT gullies are walkable and wheelchair passable.

RECYFIX®
PRO

RECYFIX®
PLUS

RECYFIX®
STANDARD

Facade Drainage

SLOTTED
CHANNELS

RECYFIX® POINT
FASERFIX® POINT

RECYFIX®
GREEN

TOP X